

AMENDMENTS TO THE CLAIMS

The following is a complete, marked up listing of revised claims with a status identifier in parentheses, underlined text indicating insertions, and strikethrough and/or double brackets indicating deletions.

Listing of the Claims:

1. (Currently Amended) Device in a cable tie, comprising:
 - an elongate band part-(2) of a ~~certain~~ width and thickness, ~~which~~ at one end ~~the elongate band part has~~ including an elongate insertion part, relatively -(3) narrower than the elongate band part-(2) and terminating in a grip tab-(4), and at ~~an~~ its other end ~~the elongate band part~~ including ~~has~~ a locking head, ~~the locking head~~ -(1) ~~with, including~~ on the one hand, a through-opening, (6) ~~which is intended~~ for the elongate band part-(2) and ~~is somewhat~~ relatively wider than the elongate band part (2) and ~~has including~~ a height ~~somewhat relatively~~ greater than ~~the a~~ thickness of the elongate band part-(2), ~~and on the other hand and~~ a slot-shaped recess (7) in ~~one transverse~~ a wall of the through-opening-(6), the width of ~~which the slot-shaped recess is being~~ such that ~~it will~~ to allow the elongate insertion part (3) to be inserted into the through-opening (6) via the slot-shaped recess (7), forming a band loop, ~~there being~~ the elongate band part further including toothing (10) on the elongate band part (2) and a locking tongue (8) provided with toothing (9) in the locking head-(1), ~~which are designed~~, by means way of a positive interlock, to lock the elongate band part (2) in relation to the locking head-(1), ~~characterised in that wherein~~, in ~~the an~~ area around ~~the a~~ connection of the elongate insertion part (3) to the grip tab, (4) ~~there are~~ wing-like projections (11) extending transversely and out from the elongate insertion part-(3), ~~which are the wing-like projections being relatively thinner than the grip tab to create a clearance interval between the elongate insertion part and the locking tongue (4) and which the wing-like projections, towards the latter grip tab, terminate in a ridge (12), which ridge in forming the band loop is designed, with the wing-like projections being projections (11) inserted into the through-opening (6) of the locking head-(1) and bearing against the opposing walls of the through-opening (6), to abut the locking head-(1), the fact that the projections (11) are thinner than the grip tab (4) creating a clearance interval (13) between the insertion part (3) and the locking tongue (8).~~

2. (Currently Amended) Device according to ~~Claim-claim~~ 1, characterised in ~~that~~wherein the projections ~~11~~ are incorporated into the grip tab ~~(4)~~.